

Piazza Grey

QUARRY TILE · 6" × 6" AND 8" × 8" WITH FULL COVE BASE AND BULLNOSE TRIM · **QUICK SHIP** · **STOCKED IN THE USA**

A warm grey, through-body quarry tile made in the USA for hard-working floors: locker rooms, back of house, commercial kitchens and exterior walks. Matching round-top sanitary cove base, inside and outside corners and bullnose give a clean, cleanable floor-to-wall finish.



Smooth



Abrasive

TECHNICAL DATA

MATERIAL	Unglazed quarry tile, through-body color, made in the USA
SURFACES	Smooth matte; abrasive (grip) for ramps and wet areas
THICKNESS	1/2"
WATER ABSORPTION	< 3.0% (ASTM C373)
BREAKING STRENGTH	> 400 lbf (ASTM C648)
SCRATCH HARDNESS	7.0 Mohs
CHEMICAL RESISTANCE	Resistant (ASTM C650)
SLIP RESISTANCE	Wet DCOF ≥ 0.42 interior; ≥ 0.60 exterior; ≥ 0.65 ramps (abrasive)
WEAR / SHADE	Class 4 commercial · V3 high shade variation
USE	Floors, walls, showers, kitchens, exterior (freeze-thaw)

FIELD TILE, TRIM AND SPECIAL PIECES

PIECE	SIZE	SURFACE	PCS / CARTON
Field tile	6" × 6"	Smooth or abrasive	44 (11.00 SF)
Field tile	8" × 8"	Smooth or abrasive	25 (11.11 SF)
Round-top sanitary cove base	5" × 6"	Smooth	44
Cove base outside corner, right	5" × 6"	Smooth	20
Cove base outside corner, left	5" × 6"	Smooth	20
Cove base inside corner	1" × 5"	Smooth	25
Cove base (tall)	5" × 8"	Smooth	24
Bullnose	6" × 6"	Smooth or abrasive	44
Bullnose corner	6" × 6"	Smooth or abrasive	44
Bullnose	8" × 8"	Smooth	25
Bullnose corner	8" × 8"	Smooth	25

Cove base and corners are sized to the 6" × 6" floor tile and set in the standard 90° position; 5" × 8" cove base is the taller option. Grout joint 3/8" recommended; use a grout release before grouting. Select tile from several cartons and blend. Made to ANSI A137.1. Tile and trim may vary from samples; confirm from actual tile before installation.